


COMMERCIAL ITEM DESCRIPTION

FUSE, INCLOSED LINK, THIN-FILM, SURFACE MOUNT (SM),  
1206 SIZE, VERY FAST ACTING

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.


1. SCOPE. This CID covers the general requirements for very fast acting, surface mount, thin-film, inclosed link fuse in a 1206 chip size. Fuses covered by this CID are intended for commercial/industrial applications.
2. CLASSIFICATION. This CID uses a classification system which is included in the Part Identification Number (PIN) as shown in the following example (see 7.1).



3. SALIENT CHARACTERISTICS.

- 3.1 Interface and physical dimensions. Fuses supplied to this CID shall be as specified herein (see figure 1).
- 3.2 Electrical specifications.
  - 3.2.1 Ampere rating. The ampere rating shall be as specified in table I.
  - 3.2.2 Voltage rating. The voltage rating shall be as specified in table I.
  - 3.2.3 Interrupting ratings. The interrupting rating shall be 50 amperes at rated voltage for ampere ratings of 0.125 ampere through 3 ampere and 35 amperes at rated voltage for ampere ratings of 4 amperes through 7 amperes.
  - 3.2.4 Opening time characteristics. The opening time characteristics shall be as indicated in table II.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Supply Center, Columbus, ATTN: DSCC-VAT, Post Office Box 3990, Columbus, OH 43213-1199, or telephone (614) 692-0548, or facsimile (FAX) (614) 692-6939.



Inches	mm	Inches	mm	Inches	mm
.005	0.13	.045	1.14	.125	3.18
.006	0.15	.060	1.52	.150	3.81
.010	0.25	.065	1.65	.190	4.83
.025	0.64	.080	2.03		
.044	1.12	.098	2.49		

NOTES:

1. Dimensions are in inches.
2. Tolerance is  $\pm .005$  inch ( $\pm 0.13$  mm), unless otherwise specified.

FIGURE 1. Configuration and dimensions.

TABLE I. Electrical characteristics.

AA59550/02-	Ampere rating	Nominal voltage rating (Vac/dc)	Nominal resistance cold ohm <u>1/</u>	Nominal voltage drop (V) <u>2/</u>
001	1/8	125	2.30000	0.200
002	2/10	125	0.93800	0.175
003	1/4	125	0.62500	0.160
004	3/8	125	0.37500	0.138
005	1/2	63	0.24050	0.130
006	3/4	63	0.13700	0.120
007	1	63	0.09950	0.115
008	1 1/4	63	0.07475	0.108
009	1 1/2	63	0.06250	0.101
010	1 3/4	63	0.05000	0.096
011	2	63	0.03975	0.093
012	2 1/2	32	0.03065	0.087
013	3	32	0.02625	0.080
014	4	24	0.01926	0.070
015	5	24	0.01375	0.065
016	7	24	0.00925	0.060

1/ Measured at 10 percent of rated current, 25°C.

2/ Measured at 100 percent of rated current, 25°C.

3/ Measured at rated voltage.

TABLE II. Opening time characteristics.

Percent of ampere rating	Opening time at 25°C
100 percent	4 hours, minimum
200 percent	5 seconds, maximum
300 percent	0.2 seconds, maximum

3.3 Environmental specifications. Fuses supplied to this CID shall be subject to the following tests and there shall be no electrical or mechanical damage to the fuse.

3.3.1 Operating temperature. The operating temperature shall be -55°C to +125°C.

3.3.2 Vibration. Fuses shall withstand 10 Hz - 55 Hz in accordance with method 201A, MIL-STD-202 and 10 Hz - 2000 Hz at 20 G's in accordance with method 204D, condition D of MIL-STD-202.

3.3.3 Insulation resistance (after opening). The insulation resistance after opening shall be greater than 10 kilo ohms.

3.3.4 Resistance to soldering heat. Fuses shall be able to withstand 60 seconds above 200°C up to 260°C, maximum.

3.3.5 Thermal shock. Fuses shall be able to withstand 5 cycles of -55°C to +125°C.

3.4 Physical specifications.

3.4.1 Materials. Fuses shall have an epoxy substrate body, Copper/Nickel/Tin-lead (95/5), cover coat of conformal coating.

3.4.2 Soldering parameters. Fuses shall be able to withstand, without electrical or mechanical damage to the fuse, a wave solder of +260°C (+500°F) for 10 seconds maximum, and a reflow solder of +260°C (+500°F) for 30 seconds maximum.

3.5 Marking. Fuses supplied to this CID shall be marked with the manufacturer's (MFR's) standard commercial PIN.

3.6 Recycled/recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. REGULATORY REQUIREMENTS. This section is not applicable to this CID sheet.

5. QUALITY ASSURANCE PROVISIONS. Quality assurance provisions shall be as specified in A-A-59550.

6. PACKAGING. Packaging shall be as specified in A-A-59550. In addition, fuses may be supplied individually or in a quantity of 3,000 on an .315 inch (8 mm) wide tape reel in accordance with EIA-RS 481-1.

7. NOTES.

7.1 PIN. The PIN should be used for Government purposes to buy commercial products to this CID. See section 2 for PIN format example.

7.2 Commercial and Government Entity (CAGE) code. For ordering purposes, inventory control, and submission of these fuses to DSCC under the Military Parts control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used.

7.3 Source of documents.

Military standards

MIL-STD-202 - Test Methods for Electronic and Electrical Component Parts.

(Copies of federal specifications and standards are available from the Document Automation and Production Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Commercial Item Description

A-A-59550 - Fuse, Inclosed Link, Thin Film, Surface Mount (SM), General Requirements for.

(Copies of commercial item descriptions are available from the Defense Printing Service Detachment Office, Building 4D (Customer Service), 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Other Publications

AMERICAN NATIONAL STANDARDS INSTITUTE/ELECTRONICS INDUSTRIES ALLIANCE (ANSI/EIA)

ANSI/EIA-481-1 - Taping of Surface Mount Components for Automatic Placement.

(Applications for copies should be addressed to the American National Standards Institute, 11 West 42nd Street, New York, NY 10036-8002.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

7.4 Ordering data. Ordering data shall be as specified in A-A-59550.

7.5 Commercial products. As part of the market analysis and research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

<u>Manufacturer's CAGE</u>	<u>Manufacturer's name and address</u>
75915	Littelfuse Incorporated 800 E. Northwest Highway Des Plaines, IL 60016-3096 (847) 824-1188

7.6 Part number (P/N) supersession data. This CID supersedes the following manufacturers' P/N's as shown. This information is being provided to assist in reducing proliferation in the government inventory system.

TABLE II. P/N supersession data.

CID dash number (see table I)	Vendor commercial P/N <u>1/</u>	
	MFR's CAGE	MFR's P/N <u>1/</u>
AA59550/02-		
001	75915	429.125
002	75915	429.200
003	75915	429.250
004	75915	429.375
005	75915	429.500
006	75915	429.750
007	75915	429001
008	75915	4291.25
009	75915	42901.5
010	75915	4291.75
011	75915	429002
012	75915	42902.5
013	75915	429003
014	75915	429004
015	75915	429005
016	75915	429007

1/ The manufacturer's P/N shall not be used for procurement to the requirements of this CID. At the time of preparation of this CID, the aforementioned commercial products were reviewed and could be replaced by the CID P/N shown.

A-A-59550/2

7.7 Government users. To acquire information on obtaining these fuses from the Government inventory system, contact Defense Supply Center, Columbus, ATTN: DSCC-CSBA, Post Office Box 3990, Columbus, OH 43216-5000, or telephone (614) 692-8508.

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - 7FXE

Preparing Activity:

DLA-CC

Project 5920-0615-02