

MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, FLEXIBLE, COAXIAL,
50 OHMS, M17/161-00001

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the cable described herein shall consist of this specification and the latest issue of MIL-C-17.




FIGURE 1. Configuration.

TABLE I. Description.

Components	Construction details										
Inner conductor	Solid bare copper wire. Overall diameter: 0.192 inch \pm 0.002.										
Dielectric core	Type F-1: Solid extruded PTFE. Diameter: 0.620 inch \pm 0.005.										
Outer conductor	Single braid of AWG #32 bare copper wire. Diameter: 0.670 inch maximum. <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;"></td> <td style="text-align: center;">Alternate</td> </tr> <tr> <td>Coverage : 96.8% nominal</td> <td style="text-align: right;">97.1% nominal</td> </tr> <tr> <td>Carriers : 36</td> <td style="text-align: right;">48</td> </tr> <tr> <td>Ends : 10</td> <td style="text-align: right;">8</td> </tr> <tr> <td>Picks/inch: 5.6 \pm10%</td> <td style="text-align: right;">5.6 \pm10%</td> </tr> </table>		Alternate	Coverage : 96.8% nominal	97.1% nominal	Carriers : 36	48	Ends : 10	8	Picks/inch: 5.6 \pm 10%	5.6 \pm 10%
	Alternate										
Coverage : 96.8% nominal	97.1% nominal										
Carriers : 36	48										
Ends : 10	8										
Picks/inch: 5.6 \pm 10%	5.6 \pm 10%										
Barrier tapes	Type FF-2: Two wraps of PTFE tape, 0.006 inch thick each, by 1 to 1-1/4 inch wide, with an approximate lay of 24 turns per foot and with 1/2 inch lap.										
Jacket	Type V: Double braid of fiberglass. Diameter: 0.730 inch \pm 0.015.										

CAUTION IS DIRECTED TO THE APPLICATION OF THIS CABLE ABOVE 400 MHZ. ATTENUATION IS TESTED ONLY AT 400 MHZ. SRL AND POWER HANDLING CAPABILITIES ARE NOT STIPULATED HEREIN.

ENGINEERING INFORMATION:

Continuous working voltage: 5,200 Vrms, maximum.

Velocity of propagation: 69.5 percent, nominal.

Operating temperature range: -55° to +250°C.

Inner conductor properties:

DC resistance (maximum at 20°C): 0.0293 ohm per 100 feet.

Elongation: 25 percent, minimum.

Tensile strength: Not applicable.

Engineering note: This cable is useful in general purpose high temperature applications. (See connector series "C" and "SC" per MIL-C-39012, and "LT" per MIL-C-26637.)

REQUIREMENTS:

Dimensions, configuration, and descriptions: See figure 1 and table 1.

Environmental and mechanical:

Visual and mechanical examination: Applicable.

Out-of-roundness: Not applicable.

Eccentricity: 10 percent, maximum.

Adhesion of conductors:

Inner conductor to core: 4 pounds, minimum; 15 pounds, maximum.

Aging stability: +250° ±5°C.

Stress crack resistance: Not applicable.

Outer conductor integrity: Not applicable.

Cold bend: Not applicable.

Dimensional stability: +250° ±5°C.

Inner conductor from core: 0.062 inch, maximum.

Inner conductor from jacket: 0.125 inch, maximum.

Contamination: Not applicable.

Bendability: Not applicable.

Flammability: Applicable.

Weight: 0.650 pound per foot, maximum.

Electrical:

Continuity: Applicable.

Spark test: Not applicable.

Voltage withstanding: 10,000 Vrms, minimum.

Insulation resistance: Not applicable.

Corona extinction voltage: 7,000 Vrms, minimum.

Characteristic impedance: 50 ±2 ohms.

Attenuation: 2 dB/100 ft maximum at 400 MHz.

Structural return loss: Not applicable.

Capacitance: 29.3 pF per foot, nominal.

Capacitance stability: Not applicable.

Capacitance unbalance: Not applicable.

Transmission unbalance: Not applicable.

Phase stability: Not applicable.

Mechanically induced noise voltage: Not applicable.

Time delay: Not applicable.

Part number: See table II.

Supersession data: See table II.

TABLE II. Cross reference of part number.

Part number	Superseded part number
M17/161-00001	RG-211A/U per MIL-C-17D (RG-117A/U canceled)

Custodians:
 Army - CR
 Navy - EC
 Air Force - 85

Preparing activity:
 Army - CR
 (Project 6145-0814-7)

Review activities:
 Army - AR, MI
 Navy - SH
 Air Force - 11, 17, 99
 DLA - ES, IS

User activities:
 Army - AT, ME
 Navy - AS, MC, OS
 Air Force - 19

Agent:
 DLA - ES