

MILITARY SPECIFICATION  
CONNECTORS, ELECTRICAL, CIRCULAR, HIGH DENSITY, QUICK  
DISCONNECT, ENVIRONMENT RESISTING: AND ACCESSORIES  
GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-C-81511F(AS) dated 30 September 1992.

SPECIFICATION SHEETS

- MIL-C-81511/1 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Receptacle, Flange Mount, Crimp-Type Contacts, Class A, F, E and W (Series 2).
- MIL-C-81511/3 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: And Accessories: Receptacle. Jam Nut Mount, Crimp-Type Contacts, Class A, F, E, and W (Series 2).
- MIL-C-81511/5 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: And Accessories: Receptacle, Cable Connecting, Crimp-Type Contacts, Class A, F,E, and W (series 2).
- MIL-C-81511/6 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: And Accessories: Plug, Crimp-Type Contacts, Class A, F, E and W (Series 2).
- MIL-C-81511/13 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: F Adapter, Rotatable, Type I (Series 1 or 2)
- MIL-C-81511/14 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; And Accessories: Adapter, Straight
- MIL-C-81511/15 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; And Accessories: Plug, Sealing Contact (Series 1 or 2)
- MIL-C-81511/16 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting and Accessories: Cap, Protective Locking

MIL-C-81511F(AS)  
SUPPLEMENT 1

- MIL-C-81511/17 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Cover, Protective, Plug (Series 2).
- MIL-C-81511/18 - Connectors, Electrical Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Cover, Protective, Receptacle (Series 1 or 2).
- MIL-C-81511/19 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting, and Accessories; Receptacle, Dummy Stowage, For Series 2 Connectors.
- MIL-C-81511/20 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; And Accessories: Nut, Slotted Hexagon, Connector Mounting, For Series 1 and 2
- MIL-C-81511/21 - Connectors, Electrical, Circular, High Density Quick Disconnect, Environment Resisting; and Accessories: Receptacle, Flange Mount, Crimp-Type Contacts, Class A, F, E and W (Series 1).
- MIL-C-81511/23 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Receptacle, Jam Nut Mount, Crimp-Type Contacts, Class A, F, E and W (Series 1).
- MIL-C-81511/25 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Receptacles, Cable Connecting, Crimp-Type Contacts, Class A, F, E and W (Series 1).
- MIL-C-81511/26 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting; and Accessories: Plug, Crimp-Type Contacts, Class A, F, E and W (Series 1).
- MIL-C-81511/41 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Flange Mount, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 3).
- MIL-C-81511/45 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Cable Connecting, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 3).
- MIL-C-81511/49 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Jam Nut Mount, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 3).

MIL-C-81511F(AS)  
SUPPLEMENT 1

- MIL-C-81511/51 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Flange Mount, Individual Release, Crimp-Type Contacts. Class A, W, and F (Series 4).
- MIL-C-81511/53 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Jam Nut Mount, Individual Release, Crimp-Type Contacts. Class A, F and W (Series 4).
- MIL-C-81511/54 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Jam Nut Mount. Solder-Type Contacts, Pins Only. Class D (Series 4).
- MIL-C-81511/55 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Receptacle, Cable Connecting, Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 4).
- MIL-C-81511/56 - Connectors, Electrical, Circular, High Density, Quick Disconnect, Environment Resisting: Plug. Individual Release, Crimp-Type Contacts. Class A, F, and W (Series 4).
- MS3425 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 8
- MS3426 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 10
- MS3428 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 14
- MS3429 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 16
- MS3430 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 18
- MS3431 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 20
- MS3432 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 22
- MS3433 - Insert Arrangements, MIL-C-81511 Electric Connector, Size 24
- MS3482 - Tool, Connector Assembly; for MIL-C-81511 Connectors

Preparing activity:  
Navy - AS