

DETAIL SPECIFICATION SHEET

ANTENNA, BLADE, L-BAND, (4 HOLE MOUNT, N CONNECTOR)

This amendment forms a part of MIL-DTL-25708/5B, dated 23 July 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

FIGURE 1, Dimensions table and NOTES: replace with the following:

Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
A	.480	.500	12.19	12.70
B	.970	.990	24.64	25.15
C	.84	.90	21.3	22.9
D	1.72	1.78	43.7	45.2
E	1.780	1.820	45.21	46.23
F	2.59	2.65	65.8	67.3
G	3.590	3.610	91.19	91.69
H	5.22	5.28	132.6	134.1
K	.191 DIA THRU	.201 DIA THRU	4.85 DIA THRU	5.11 DIA THRU
L	---	2.00	---	50.8
M	---	1.00	---	25.4
N	.31 R ref		7.9 R ref	
P	---	3.32	---	84.3
Q	.06 R	.09 R	1.5 R	2.3 R
R	---	.53	---	13.6
S	.41	---	10.5	---
T	.31 R ref		7.9 R ref	
U	1.11	1.15	28.2	29.2
V	---	1.88	---	47.8
W	---	3.75	---	95.2
X	---	.61	---	15.5
Y	.120	.150	3.05	3.81
Z	---	.22	---	5.6
AA	---	.44	---	11.2
AB	.50 R ref		12.7 R ref	
AC	.50 R ref		12.7 R ref	

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerances on two place decimals are ± .02 inch and tolerances on three place decimals are ± .005 inch.

MIL-DTL-25708/5B
AMENDMENT 2

PAGE 3

Change concluding material to be consistent with the following:

Custodians:

Army - CR
Navy - AS
Air Force - 11
DLA - CC

Review activity:

Army - AV
Air Force - 99

Preparing activity:

DLA - CC

(Project No. 5985-1257-04)