

MILITARY SPECIFICATION SHEET
FLANGES, WAVEGUIDE (CHOKE)
(SQUARE, 4 HOLE)

This amendment forms a part of MIL-F-3922/69, dated 3 February 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Insert text box:

This specification sheet is inactive for new design since 8 May 1998.

Delete second sentence of preamble and substitute: "The requirements for acquiring the flanges herein shall consist of this document and MIL-DTL-3922."

Insert at bottom of page:

"AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited."

PAGE 2

Delete "ANSI-B46.1-1962" and substitute "ASME B46.1".

PAGE 3

Delete footnotes 4/ and 5/ and substitute:

4/ Material shall be aluminum alloy 6061-T6 (ASTM-B241/B241M, ASTM-B221, SAE-AMS-QQ-A-200/8, SAE-AMS-QQ-A-225 and ASTM-B211)."
5/ Material shall be aluminum alloy 6063-T6 (ASTM-B241/B241M, ASTM-B221 and SAE-AMS-QQ-A-200/9)."

PAGE 6

Add concluding material consistent with the following:

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project No. 5985-1273)

Review activities:
Army - AR, AV, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 99