

MILITARY SPECIFICATION
SWITCHES, WAVEGUIDE
GENERAL SPECIFICATION FOR

This supplement forms a part of Military Specification MIL-S-55041C dated 10 January 1984.

SPECIFICATION SHEETS

- MIL-S-55041/2 - Switch, Waveguide, 1P2T, Type SA-1435/U.
- MIL-S-55041/3 - Switches, Waveguide, 2P2T, Fail-safe.
- MIL-S-55041/4 - Switches, Waveguide, Transfer, Latching.
- MIL-S-55041/5(USAF) - Switch, Waveguide, Electromechanical, Fail-safe, Frequency range 8.5 - 10.3 GHz.
- MIL-S-55041/6 - Switches, Waveguide, 1P2T, Fail-safe.
- MIL-S-55041/7 - Switches, Waveguide, 2P2T, Fail-safe.
- MIL-S-55041/8 - Switches, Waveguide, 2P2T, Fail-safe, 115 volts, AC.
- MIL-S-55041/9 - Switches, Waveguide, 1P2T, Manually Operated.
- MIL-S-55041/10(USAF) - Switch, Waveguide, Electromechanical, Latching, Frequency range 8.6 - 10.3 GHz.
- MIL-S-55041/11 - Switches, Waveguide, 1P2T, Latching.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5985-0975-8)