

MILITARY SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, RECTANGULAR, RACK TO PANEL,
ENVIRONMENT RESISTING, 150°C CONTINUOUS OPERATING
TEMPERATURE, MULTIPLE INSERTS

This specification is approved for use by all Depart-
ments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall
consist of this specification sheet and the issue of the following
specification listed in that issue of the Department of Defense
Index of Specifications and Standards (DODISS) specified in the
solicitation: MIL-C-83527.

REQUIREMENTS:

Inserts: The inserts shall conform to the requirements of MIL-C-83527,
DOD-STD-1842, and the specification part or identifying numbers (PIN)
indicated in table I.

TABLE I. Inserts.

PIN	Cavities A, C, and E	PIN	Cavities B, D, and F
M83527/07-01	I-150	M83527/07-06	II-100
M83527/07-02	I-70C1	M83527/07-07	II-11C2
M83527/07-03	I47T2	M83527/07-08	II-20T4
M83527/07-04	I-24	M83527/07-09	II-34
M83527/07-05	I-60	M83527/07-10	II-T6

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85

Preparing activity:
Air Force - 85
Agent
DLA - ES

Review activities:
Army - AR, MI
Navy - EC, MC, OS
Air Force - 11, 15, 17, 99
DLA - ES

(Project 5935-3666-01)