

PERFORMANCE SPECIFICATION SHEET

FUSES, INSTRUMENT, POWER, AND TELEPHONE
(NONINDICATING), STYLE F60

This amendment forms a part of MIL-PRF-15160/60G, dated 13 February 1998, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

TABLE I, delete and substitute:

"TABLE I. Type designation. ^{1/}

Style	Characteristic	Voltage	Current
F60	C	500V	1/8A
F60	C	500V	1/4A
F60	C	500V	3/8A
F60	C	500V	1/2A
F60	C	500V	3/4A
F60	C	500V	1A
F60	C	500V	2A
F60	C	500V	3A
F60	C	500V	5A
F60	C	500V	6A
F60	C	500V	8A
F60	C	500V	10A
F60	C	500V	15A
F60	C	500V	20A
F60	C	500V	25A
F60	C	500V	30A

^{1/} For silver plated terminals, the designator "S" is added after the current rating."

Custodians:
 Army - CR
 Navy - SH
 Air Force - 85

Preparing activity:
 DLA - CC
 (Project 5920-0602)

Review activities:
 Army - AR, CR4, MI
 Navy - AS, CG, MC, OS, YD2
 Air Force - 11, 19, 99