



User activities: Army - WC, ME, SL
Navy - AS, MC, SH
Air Force - 19

Reviewer activities: Army - M, MU, SL
Navy - OS
Air Force - 11, 17, 80
OSA-ES

RATINGS

Style	LT10
Grade	1
Class	A
Temperature rise	15° C
Ambient temperature	90° C
Operating temperature	-55° to +105° C
Dielectric withstanding Voltage (sea level)	1000 volts rms for a minimum of 60 sec.
Dielectric withstanding Voltage (reduced barometric pressure)	200 volts rms for a minimum of 60 sec.
Terminal pull	5 pounds
Altitude	70,000 feet
Weight	2.8 grams max.

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses	
	Minimum	Maximum
A	.300 (7.62)	.320 (8.13)
B	.550 (13.97)	.570 (14.48)
C	1.250 (31.75)	1.625 (41.28)
D	.026 (.66)	.030 (.76)

ELECTRICAL CHARACTERISTICS (INITIAL)

Dash No. 1/	Type designation 2/	Former type designation	Superseded MS part no.	Inductance ±10% uh	D min	Test freq. MHz	Self-resonant frequency Min MHz	DC resistance Max Ohms	Rated DC current Ma
-1	LT10K143	LT4K059	MS75053-1	180	80	.790	6.0	5.5	148
-2	LT10K144	LT4K060	-2	220	80	.790	5.5	5.9	145
-3	LT10K145	LT4K061	-3	270	80	.790	5.1	6.6	138
-4	LT10K146	LT4K062	-4	330	75	.790	4.2	7.8	122
-5	LT10K147	LT4K063	-5	390	75	.790	3.9	8.7	118

- 1/ The dash number added to the MS military-standard number constitutes the MS part number; for example, MS 14048-1.
- 2/ The decrease in maximum operating temperature from 125° C to 105° C does not downgrade these coils but assures satisfactory operation at 105° C for a minimum of 2000 hours of life rather than a shorter period of operation at 125° C.

This military standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

APPROVED 15 February 1972 REVISED

P.A. NAVY-EC Other Cust AF-80 ARMY-EL	International Interest	TITLE Coils, radio frequency, molded, fixed, subminiature (iron core) types LT10K143 to LT10K147 incl.	MILITARY STANDARD MS14048
Procurement Specification MIL-C-15305	SUPERSEDES: MS75053		SHEET 1 OF 2

Electrical Characteristics (Final)

Inspection Group	Allowable variation from initial measurement		Allowable % from specified minimum value in Electrical Characteristics (Initial) table	
	Inductance Percent	DC resistance	Self-resonant frequency	Q
Qualification Inspection				
Group II	± 2	--	--	- 10
Group III	± 5	± (3% + .001ohm)	- 8	- 10
Group IV	± 5	± (2% + .001ohm)	- 10	- 15
Quality Conformance Inspection				
Group C				
Subgroup I	± 2	--	--	- 10
Subgroup II	± 5	± (2% + .001ohm)	- 10	- 15
Subgroup III	± 5	± (3% + .001ohm)	- 8	- 10

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. These coils are intended to be mounted by the body.
4. The polarizing voltage during the moisture-resistance tests is applied with the positive lead connected to the coil terminals tied together, and the negative lead connected to the metal strap.
5. Terminal strength (Pull) test, is not applicable in "Group B" inspection Table VI.
6. Solderable/weldable lead wire, AWG #21.
7. Barometric pressure test (test condition C) is applicable.
8. Shock, specified pulse, method 213, test condition I, is applicable.
9. Referenced document shall be the issue in effect on date of invitation for bid.
10. This standard takes precedence over the procurement specification referenced herein.

REVISED

APPROVED

P.A. NAVY-EC	International interest	TITLE Coils, radio frequency, molded, fixed, subminiature (iron core) types LT10K143 to LT10K147 incl.	MILITARY STANDARD
Other Cust AF-80 ARMY-EL			MS14048
Procurement Specification MIL-C-15305	SUPERSEDES:	MS75053	SHEET 2

DD FORM 10 APR 64 672 (Coordinated) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

User activities: Army
Navy
Air Force

Activities: Army
Navy
Air Force

This standard is mandatory for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.