

NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/334C
 17 January 1986
 SUPERSEDING
 MIL-T-27/334B
 16 January 1985

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 25 VOLTAMPERES, 400 HZ, TF5S03ZZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformer described herein shall consist of this specification and the latest issue of MIL-T-27.



NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the top and sides of case.
4. Dimensional tolerance shall be ±.02 unless otherwise specified.
5. For series output connect terminals 4 and 5 together. For parallel output connect pins 3 to 4 and 5 to 6.

INCHES	MM
.02	0.5
.05	1.3
.09	2.3
.17	4.3
.170	4.32
.35	8.9
1.05	26.7

FIGURE 1. Dimensions and configurations.

MIL-T-27/334C

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2): 115 volts rms, 400 ±20 hertz.

Secondary voltage and current (3-6): See table I.

Voltampere: 25 voltamperes.

Working voltage (1-2): 535 volts peak.

Design and construction

Dimensions and configuration: See figure 1.

Duty cycle: Continuous.

Case: Encapsulated.

Material: Epoxy fiberglass.

Terminals: Turret type.

Height: .170 inch, maximum.

Weight .52 pound, maximum.

Operating temperature range -55°C to +130°C.

Altitude. 70,000 feet.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Dielectric withstanding voltage (each winding, secondary windings connected in series):

At sea level: 1500 volts rms.

At reduced barometric pressure 1.25 times the peak working voltage specified.

Electrical characteristics:

Rated load: With 115 volts rms and 400 Hz in (1-2), and rated current in secondary, the voltage across (3-6) shall be as specified in table I, ±5 percent.

Efficiency. 90 percent minimum at rated load.

Temperature rise. 35°C with 115 volts rms, 400 hertz across (1-2) at an ambient temperature of 95°C, full load terminals (3-6).

Regulation:
$$\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100$$

Shall not exceed 10 percent

Polarity Additive, with terminals 2 and 3, and 5 and 4 connected.

Marking location See figure 1.

Part number M27/334- (dash number from table I).

TABLE I. Electrical ratings.

Dash number M27/334	Secondary voltage (3-6) (V rms)		Secondary current (3-6) (amperes)	
	Series (CT)	Parallel	Series	Parallel
01	10	5	2.50	5.00
02	12.6	6.3	2.00	4.00
03	16	8	1.56	3.12
04	20	10	1.25	2.50
05	24	12	1.04	2.08
06	34	17	0.735	1.47
07	40	20	0.625	1.25
08	56	28	0.446	0.892
09	88	44	0.284	0.568
10	120	60	0.208	0.416

QUALITY ASSURANCE PROVISIONS.

Extent of Qualification.

Qualification testing and approval to M27/332-10 and M27/337-10 shall be sufficient to grant qualification approval to MIL-T-27/332 through MIL-T-27/337 inclusive, all parts.

Qualification testing and approval to M27/334-10 shall be sufficient to grant qualification approval to M27/334-01 through M27/334-10.

Revision letters are not used to denote changes due to the extensiveness of the changes.

Custodians:

Army - ER
Navy - EC
Air Force - 85

Preparing activity:

Army - ER

Agent:

DLA - ES

Review activities:

Army - AR
Navy - OS
Air Force - 11, 17, 99
DLA - ES

(Project 5950-0658-03)

User activities:

Army - ME
Navy - AS, MC
Air Force - 19