

NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND


MIL-PRF-27/337D
 22 January 1992
 SUPERSEDING
 MIL-T-27/337C
 17 January 1986

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS, POWER, 150 AND 200 VOLT AMPERES,
 400 HZ, TF5S03ZZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-T-27.



Inches	mm
.02	0.5
.09	2.3
.30	7.6
.40	10.2

Ltr	Dimensions	
	Inches	mm
A	2.43 ±.02	(50.8) ±(.5)
B	2.00 ±.02	(41.1) ±(.5)
C	2.10 ±.02	(46.0) ±(.5)
D	1.93 ±.02	(38.1) ±(.5)
E	1.50 ±.02	(28.4) ±(.5)
F	.25 ±.04	(6.4) ±(1.0)
H	1.90 ±.04	(38.1) ±(1.0)
J	.21 ±.04	(42.9) ±(1.0)
K	.138-32 UNC 2B	

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking shall be on the top and sides of case.
4. Dimensional tolerance shall be ±.02 unless otherwise specified.
5. For series output connect terminals 4 and 5 together. For parallel output connect pins 3 to 4 and 5 to 6.

FIGURE 1. Dimensions and configuration.

MIL-T-27/337D

REQUIREMENTS: (When numbers in parentheses, i.e., (1-2) are used, they indicate the winding and the extreme terminals of the winding.)

Electrical ratings:

Primary voltage (1-2): 115 volts rms, 400 \pm 20 hertz.

Secondary voltage and current (3-6): See table I.

Voltampere: See table I.

Working voltage (1-2): 535 volts peak.

Design and construction:

Dimensions and configuration: See figure 1.

Duty cycle: Continuous.

Case: Encapsulated.

Material: Epoxy fiberglass.

Terminals: Turret type.

Height: .300 inch, maximum.

Weight: 2 pounds, maximum (PIN's -01 through -10) and 2.2 pounds, maximum (PIN's -11 through -19).

Operating temperature range: -55°C to +130°C.

Altitude: 70,000 feet.

Terminal strength: MIL-STD-202, method 211, test condition A, 2 pounds.

Dielectric withstanding voltage (each winding, secondary windings connected in series):

At sea level: 1500 volts rms.

At reduced barometric pressure: 1.25 times the peak working voltage specified.

Electrical characteristics:

Rated load: With 115 volts rms and 400 Hz in (1-2), and rated current in secondary, the voltage across (3-6) shall be as specified in table I, 5 percent.

Efficiency: 90 percent minimum at rated load.

MIL-T-27/337D

TABLE I. Electrical ratings.

Dash number M27/337	Secondary voltage (3-6) (V rms) $\pm 5\%$		Secondary current (3-6) (amperes)		Volt- ampere rating
	Series (CT)	Parallel	Series	Parallel	
-01	10	5	15	30	150
-02	12.6	6.3	11.9	23.8	150
-03	16	8	9.37	18.7	150
-04	20	10	7.50	15	150
-05	24	12	6.25	12.5	150
-06	34	17	4.41	8.82	150
-07	40	20	3.75	7.50	150
-08	56	28	2.68	5.36	150
-09	88	44	1.70	3.40	150
-10	120	60	1.25	2.50	150
-11	12.6	6.3	15.85	31.70	200
-12	16	8	12.50	25	200
-13	20	10	10	20	200
-14	24	12	8.35	16.70	200
-15	34	17	5.90	11.80	200
-16	40	20	5	10	200
-17	56	28	3.57	7.14	200
-18	88	44	2.27	4.54	200
-19	120	60	1.66	3.53	200

MIL-T-27/337D

Temperature rise: 45°C with 115 volts rms, 400 hertz across (1-2) at an ambient temperature of 85°C, full load terminals (3-6), for PIN's -01 through -10.

Temperature rise: 45°C with 115 volts rms, 400 hertz across (1-2) at an ambient temperature of 70°C, full load terminals (3-6), for PIN's -11 through -19.

Regulation:
$$\frac{\text{Voltage (no load)} - \text{Voltage (rated load)}}{\text{Voltage (rated load)}} \times 100 \text{ (Shall not exceed 10 percent.)}$$

Polarity: Additive, with terminals 2 and 3, and 5 and 4 connected.

Marking location: See figure 1.

Part or Identifying Number (PIN). M27/337-(dash number from table I).

QUALITY ASSURANCE PROVISIONS:

Extent of qualification:

Qualification testing and approval to M27/332-10 and M27/337-19 shall be sufficient to grant qualification approval to MIL-T-27/332 through MIL-T-27/337 inclusive, all parts.

Qualification testing and approval to M27/337-19 shall be sufficient to grant qualification approval to M27/337-01 through M27/337-19.

Revision letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR
Navy - OS
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - ME
Navy - AS, MC
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5950-0772)