


PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR110/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 62.5 MHz to 75 MHz; fifth mechanical overtone; noncontrolled; series resonance.



NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Crystal unit - CR110/U.

MIL-C-3098/86D

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 62.5 MHz to 75 MHz, inclusive.

Capacitance, shunt: 4 pF, maximum.

Mode of oscillation: Fifth mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Frequency tolerances:

Operating temperature range: ± 30 ppm.

Reference temperature: ± 15 ppm.

Reference temperature: $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

Operating temperature range (noncontrolled): -40°C to $+85^{\circ}\text{C}$, inclusive.

Frequency tolerance: ± 30 ppm.

Equivalent resistance: 60 ohms, maximum.

Shock (specified pulse):

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 10 percent.

Vibration: Method 204, MIL-STD-202, test condition A.

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 10 percent.

Thermal shock:

Frequency change permitted: ± 5 ppm.

Equivalent resistance change permitted: ± 10 percent.

Aging:

Frequency change permitted: ± 5 ppm.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:

Army - CR

Navy - EC

Air Force -85

Review activities:

Air Force - 17, 84

Preparing activity:

Army - CR

Agent:

DLA - CC

(Project 5955-0697-55)