

PERFORMANCE SPECIFICATION SHEET
 CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY
 (SERIES TNC (CABLED), PIN CONTACT, CLASS 2)

This amendment forms a part of MIL-PRF-39012/26G, dated 26 September 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure 1, General configuration, add the following new note 9 as follows;

"9. Three holes .027 (0.69 mm) minimum diameter, equally spaced, are required for safety wiring after mating. Location on the coupling nut optional."

PAGE 2

Figure 2, Note 3, delete in its entirety.

PAGE 3

* TABLE I, dash number "0225" only, in column 4: Delete "1.500 (38.1)" and substitute "1.739 (44.17)"

TABLE I, add the following new dash numbers;

Dash number <u>1/</u>	Applicable cable M17/ 2/	Dimensions	Inches (millimeters) maximum
Category A – Field serviceable (no special tools required) <u>3/</u>			
0030	220-00001	A	1.250 (31.75)
0130	220-00002 <u>15/</u>		
0031	221-00001		
0131	221-00002 <u>15/</u>		
0032	222-00001		
0132	222-00002 <u>15/</u>		
0033	223-00001		
0133	223-00002 <u>15/</u>		
0034	224-00001		
0134	224-00002 <u>15/</u>		
0035	225-00001		
0135	225-00002 <u>15/</u>		

PAGE 5

Add the following new note;

"15/ Armored cable."

MIL-PRF-39012/26G
AMENDMENT 5

PAGE 11

TABLE II, Group qualification, Group I, column 3: Add "-0225."

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the material notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:

DLA - CC

(Project 5935-4304)

Review activities:

Army - AR, AT, EA, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99