

INCH-POUND

MIL-PRF-39012/79F
AMENDMENT 1
5 April 2002

PERFORMANCE SPECIFICATION

CONNECTORS, PLUG, ELECTRICAL, COAXIAL, RADIO FREQUENCY, SERIES SMA (CABLED, PIN, CLASS 2, SEMIRIGID CABLE)

This amendment forms a part of MIL-PRF-39012/79F, dated 24 January 1992, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Table I, note 8/: Delete and substitute:

“8/ All corrosion-resistant steel-bodied connectors shall be gold plated in accordance with ASTM B488, type 3, grade C, class 1.27, at least in the area of solder attachment.”

PAGE 10

Table V, note 4/: Delete and substitute:

“4/ All corrosion-resistant steel-bodied connectors which are designed to be assembled to the outer conductor using solder shall be gold-plated in accordance with ASTM B488, type 3, grade C, class 1.27, at least in the area of solder attachment.”

CONCLUDING MATERIAL

Custodians:

Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:

DLA - CC

(Project 5935-4521-001)

Review activities:

Army - AM, AT, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99