

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, NONWIRE WOUND
(ADJUSTMENT TYPE, LEAD SCREW ACUATED),
NONESTABLISHED RELIABLITY, AND ESTABLISHED RELIABILITY,
STYLE RJR24

This amendment forms a part of MIL-PRF-39035/2G, dated 12 February 1998, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete and substitute:

“ Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAT, Post Office Box 3990, Columbus OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. “

PAGE 2

* 2.2.1, delete and substitute first parenthetical note:

“(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094).”

PAGES 5

Referenced dimensional equivalents, delete and substitute

| <u>Inches</u> | <u>mm</u> |
|---------------|-----------|---------------|-----------|---------------|-----------|---------------|-----------|---------------|-----------|
| 0.006 | 0.15 | 0.024 | 0.61 | 0.100 | 2.54 | 0.170 | 4.32 | 0.419 | 10.64 |
| 0.010 | 0.25 | 0.025 | 0.64 | 0.125 | 2.67 | 0.187 | 4.75 | 0.420 | 10.67 |
| 0.015 | 0.38 | 0.075 | 1.91 | 0.135 | 3.18 | 0.300 | 7.62 | | |
| 0.020 | 0.51 | 0.080 | 20.3 | 0.150 | 3.81 | 0.375 | 9.53 | | |

- * 6.2, Delete and substitute title:

"6.2 Acquisition documents."

- * 6.2, Add the following requirement

"d. Packaging requirements (see 5.1)"

Custodians:

Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:

DLA - CC

(Project 5905-1691-02)

Review activities:

Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 19, 99