

PERFORMANCE SPECIFICATION

RESISTORS, VARIABLE, NONWIRE WOUND
(ADJUSTMENT TYPE, SINGLE TURN),
NONESTABLISHED RELIABILITY, AND ESTABLISHED RELIABILITY,
STYLE RJR50

This amendment forms a part of MIL-PRF-39035/4F, dated 12 February 1998, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete and substitute:

“ Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: Defense Supply Center, Columbus, ATTN: DSCC-VAT, Post Office Box 3990, Columbus OH 43216-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter. “

PAGE 2

* 2.2.1, delete and substitute first parenthetical note:

“(Unless otherwise indicated, copies of the above specifications, standards, and handbooks are available from the Document Automation and Production Service, Building 4D (DPM-DODSSP), 700 Robbins Avenue, Philadelphia, PA 19111-5094).”

PAGE 4

Referenced dimensional equivalents, delete and substitute:

<u>Inches</u>	<u>mm</u>	<u>Inches</u>	<u>mm</u>	<u>Inches</u>	<u>mm</u>
0.001	0.025	0.016	0.41	0.110	2.79
0.002	0.051	0.020	0.51	0.250	6.35
0.010	0.25	0.025	0.64	0.312	7.92
0.015	0.38	0.100	2.54	0.375	9.53

- * 6.2, Delete and substitute title:
"6.2 Acquisition documents."
- * 6.2, Add the following requirement
"c. Packaging requirements (see 5.1)"

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC
(Project 5905-1691-04)

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS
Air Force - 19, 99