

INCH-POUND

NOTES: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

MIL-PRF-55339/25B
AMENDMENT 1
31 October 1988

PERFORMANCE SPECIFICATION

ADAPTER, CONNECTOR, COAXIAL, RADIO FREQUENCY, IN-LINE, JAMNUT
MOUNTED (BETWEEN SERIES BNC JACK TO SERIES N JACK), CLASS 2

This amendment forms a part of Performance Specification MIL-PRF-55339/25B, dated 23 March 1988, and
and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure 1: delete dimension "1.071 \pm .000 MAX. O. D." and
-.018
.022 THK

substitute: ".900 MAX OD X .022 THK, internal tooth".

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - OS, SH
Air Force - 19, 99
DLA - ES

User activities:
Army - AT
Navy - AS, MC, SH
Air Force - 19

Preparing activity:
Army - CR

Agent
DLA - ES

(Project 5935-3674)