

INCH-POUND

MIL-PRF-6106/48B
AMENDMENT 2
15 February 2003
SUPERSEDING
AMENDMENT 1
13 December 2001

PERFORMANCE SPECIFICATION SHEET

RELAY, ELECTROMAGNETIC, 100 AMPERES, SPST (N.O.), WITH SPDT (FORM Z)
5 AMPERES AUXILIARY CONTACTS, HERMETICALLY SEALED, TYPE I

This amendment forms a part of MIL-PRF-6106/48B, dated 10 November 2000, and is
Approved for use by all Departments and Agencies of the Department of Defense.

Page 5

Main contacts, current rating, lamp: Add a note after "50 amperes (25,000 life cycles)." "The total "On" time shall be 2 seconds ± 0.05 second and the "Off" time shall be 7 seconds ± 2.0 seconds for a simulated lamp load."

- * Shock, delete: "50g's (half sine wave)" and substitute "30g's (half sine wave)".

Page 6

- * Vibration sinusoidal (-001 only): Add a note after "55-2000 Hz, 10 g's." "Test to be performed with 5 ampere load on main contact."

Auxiliary contacts, current rating, lamp: Add a note after "1 ampere (25,000 life cycles)." "The total "On" time shall be 2 seconds ± 0.05 second and the "Off" time shall be 7 seconds ± 2.0 seconds for a simulated lamp load."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1207)