

INCH-POUND
MIL-PRF-83383/4D
AMENDMENT 2
15 October 2001
SUPERSEDING
AMENDMENT 1
17 December 1999

PERFORMANCE SPECIFICATION SHEET

CIRCUIT BREAKERS, REMOTE CONTROL, AC, THERMAL, TRIP-FREE,
SERIES TRIP, TRIPLE POLE, AUXILIARY CONTACTS (5 TO 100 AMPERES)

This amendment forms a part of MIL-PRF-83383/4D, dated 28 May 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, replace the maximum tripping time at 1000 percent rated current for the 20 ampere unit with 1.3 seconds.

PAGE 5

Endurance, delete and substitute:

“Endurance:

Electrical:

5 to 25 amperes: 30,000 cycles resistive or inductive or motor load or lamp load.

35 to 50 amperes: 30,000 cycles resistive or inductive or motor load or 25,000 cycles lamp load.

60 to 100 amperes: 30,000 cycles resistive or inductive load or 25,000 cycles motor load.”

Custodians:
Army - CR
Navy - AS
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5925-0310)