

MILITARY SPECIFICATION SHEET

SWITCHES, DUAL IN-LINE PACKAGE (DIP), SLIDE ACTUATOR,
SINGLE POLE, SINGLE THROW STATIONS, OPEN BASE

This amendment forms a part of MIL-S-83504/3A, dated 1 March 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Table I, delete and substitute the following:

"

TABLE I. Dash numbers and characteristics.

Dash number		Number of stations	Dimension "A" inches (mm)
Plug-in <u>1/</u>	Solderable		
001	021	1	.280 (7.11)
002	022	2	.280 (7.11)
003	023	3	.380 (9.65)
004	024	4	.480 (12.19)
005	025	5	.580 (14.73)
006	026	6	.680 (17.27)
007	027	7	.780 (19.81)
008	028	8	.880 (22.35)
009	029	9	.980 (24.89)
010	030	10	1.080 (27.43)
011	031	11	1.180 (29.97)
012	032	12	1.280 (32.51)

1/ PIN's for switches equipped with plug-in terminations are inactive for new design."

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5930-1619-03)

Review activities:
Army - AV, MI
Navy - AS, SH
Air Force - 99