

INCH-POUND

MIL-PRF-83536/12A
AMENDMENT 2
15 November 2002
SUPESEDING
AMENDMENT 1
15 August 2002

PERFORMANCE SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, ESTABLISHED RELIABILITY, DPDT,
LOW LEVEL TO 10 AMPERES, MAGNETIC LATCH, HERMETICALLY SEALED,
ALL WELDED, DC COILS

This amendment forms a part of MIL-PRF-83536/12A, dated 15 April 2002, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* FIGURE 1, Raised Vertical Flange Mount (RVFM) With Socket Pins, +y1 and -y1 tolerance:
Delete "+.020" and substitute "+.000"
+.000" -0.020".

PAGE 4

FIGURE 1, Mounting Hole Layout RVFM and HFM (2 places): Delete "1.046" and substitute "1.406".

The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based upon the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC
(Project 5945-1203)