

INCH-POUND

MIL-R-83726/12D
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION SHEET

RELAYS, HYBRID, TIME DELAY (ON RELEASE), TYPE IIA,
CLASS B, 10 AMPERES, 4PDT, HERMETICALLY SEALED,
FIXED TIME, 0.100 TO 300 SECONDS

Inactive for new design after 10 January
1994. Refer to MIL-R-83726/29 for new
designs.

This amendment forms a part of MIL-R-83726/12D, dated 27 March 1995, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Table I heading, delete "2".

Footnote 2, delete.

PAGE 4

Transients: delete and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

Spike, delete.

Footnote 2 and 3, delete.

PAGE 6

PIN: delete "a four-digit dash number (expressed in milliseconds), and a quality level indicator" and substitute "and a four-digit dash number (expressed in milliseconds)".

Quality level indicator, delete.

Examples: delete and substitute "M83726/12-1000 - 100 millisecond time delay,
M83726/12-1001 - 1 second time delay".

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1077-03)

Review activities:
Air Force - 99