

INCH-POUND

MIL-R-83726/23C
AMENDMENT 1
15 February 2000

MILITARY SPECIFICATION SHEET

RELAYS, HYBRID, TIME DELAY (ON RELEASE), TYPE II B,
CLASS B, 10 AMPERES, 4PDT, HERMETICALLY SEALED

Inactive for new design after 10 November
1993. No superseding document.

This amendment forms a part of MIL-R-83726/23C dated 22 December 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Dash number heading, delete "2".

Footnote 2/, delete.

PAGE 4

Figure 2, delete.

PAGE 5

Figure 3, delete.

PAGE 6

Transients: delete and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

Spike, delete.

Footnote 3/ and 4/, delete.

PAGE 9

PIN: delete ", a four-digit dash number (expressed in milliseconds), and a quality level indication as follows:" and substitute "and a four-digit dash number (expressed in milliseconds)."

Quality level, delete.

Examples: delete and substitute: "M83726/23-1000 - 0.100 second time delay.
M83726/23-6001 - 6 seconds time delay.

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1077-08)

Review activities:
Air Force - 99

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

1 of 1

FSC 5945