

INCH-POUND

MIL-PRF-83726/30E
AMENDMENT 3
15 July 2002
SUPERSEDING
AMENDMENT 2
15 February 2000

PERFORMANCE SPECIFICATION SHEET

RELAY, HYBRID, TIME DELAY (ON OPERATE), CLASS B, TYPE I,
HERMETICALLY SEALED, DPDT, 10 AMPERES, ADJUSTABLE TIME
DELAY (EXTERNAL RESISTOR), 0.1 TO 500 SECONDS

This amendment forms a part of MIL-PRF-83726/30E, dated 15 June 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1. Outline dimensions and configuration of relay. delete "+" sign next to the "C1" terminal.

PAGE 2

* Figure 1, solder hook terminals, delete dimension ".300" and substitute ".310 MAX."

PAGE 4

Transients: delete "+80 volts in accordance with MIL-STD-704, figure 9, limit 1." and substitute "In accordance with MIL-STD-704 for 28 volts dc system (figure 11)."

The margins of this amendment are marked with asterisks to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-1167-08)

Review activities:
Navy - OS
Air Force - 19