

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, MICA DIELECTRIC, HIGH RELIABILITY,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-87164A, dated 24 May 1999, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 11

Table V, column 1, subgroup 1, delete "Thermal shock and immersion" and substitute "Thermal shock".

PAGE 14

4.7.4c, delete.

PAGE 16

* 4.7.13.1, delete and substitute:

"4.7.13.1 Pull test. All terminals shall be subjected for 5 seconds ± 1 second, to pull of 5 pounds +2 ounces, -0 ounces. The direction of pull shall be perpendicular to the leads for all styles except for styles CMS03 and CMS04. For styles CMS03 and CMS04, the direction of pull shall be in the direction of the leads."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - CR
Navy - EC
Air Force - 19
DLA - CC

Preparing activity:
DLA - CC
(Project 5910-2181)

Review activities:
Air Force -11