


FEDERAL SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, SPECIAL PURPOSE, CABLE OUTLET, LOCKING,
 GROUNDING, 3 POLE, 4 WIRE, 30 AMPERES, 250 VOLTS, 50/60 HERTZ, 3-PHASE

The General Services Administration has authorized the use
 of this federal specification sheet by all federal agencies.

The complete requirements for procuring the connectors described herein shall
 consist of this document and the latest issue of W-C-596/GEN.



Inches	mm
1.046	26.57
1.980	50.29
3.312	84.12
4.600	116.84

NOTES:

1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Undimensioned pictorials are for reference purposes only.

FIGURE 1. Configuration and dimensions.

W-C-596/130B

REQUIREMENTS:

Design and configuration: See figure 1.

Dimensions: Shall conform to NEMA WD 6, configuration L15-30R.

Armored construction: Not acceptable.

Ratings:

Voltage: 250 volts.

Current: 30 amperes.

Frequency: 50/60 hertz, 3-phase.

Mating connector: W-C-596/129 and /131.

Strain relief: Accommodate cable diameter .625 - 1.050 inch.

Part or Identifying Number (PIN): W-C-596/130- (dash number from table I).

Supersession and cross reference: See table II.

TABLE I. Dash number.

Dash no.	Supersedes style	Description
1		Cable outlet

TABLE II. Supersession and cross reference.

Active Government PIN	Superseded numbers		
	CAGE ^{1/} 74545	CAGE 04009	CAGE 81091
W-C-596/130-1	2723	6523 6524	L1530-C

^{1/} CAGE is the Commercial and Government Entity code which is assigned and maintained by Defense Logistics Information Service (DLIS) in Battle Creek, MI.

MILITARY INTERESTS:

Custodians

Army - CR
Navy - YD
Air Force - 11
DLA - CC

Review Activities

Army - AV, CR4, MI
Navy - AS, EC, MC, SH
Air Force - 99

CIVIL AGENCY
COORDINATING ACTIVITIES:

DCGOVT - DCG
DOT - ACO
GSA - 7FXE
HHS - FEC
USDA - AFS

Preparing Activity:
DLA - CC

(Project 5935-4305-69)