


REVISIONS			
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED
A	Changes in accordance with NOR 5962-R156-95.	95-06-16	Michael Frye
B	Changes in accordance with NOR 5962-R186-95.	95-08-25	Michael Frye
C	Changes in accordance with NOR 5962-R009-97.	96-10-04	Ray Monnin
D	Update drawing to current requirements. Editorial changes throughout. - gap	02-04-16	Ray Monnin

REV																					
SHEET																					
REV	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D		
SHEET	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32			
REV STATUS				REV			D	D	D	D	D	D	D	D	D	D	D	D	D	D	
OF SHEETS				SHEET			1	2	3	4	5	6	7	8	9	10	11	12	13	14	
PMIC N/A	PREPARED BY Kenneth Rice								DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216 http://www.dsccl.dla.mil												
STANDARD MICROCIRCUIT DRAWING THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE AMSC N/A	CHECKED BY Jeff Bowling																				
	APPROVED BY Michael Frye								MICROCIRCUIT, MEMORY, DIGITAL, CMOS, PROGRAMMABLE LOGIC ARRAY, MONOLITHIC SILICON												
	DRAWING APPROVAL DATE 94-11-21																				
	REVISION LEVEL D								SIZE A	CAGE CODE 67268	5962-94730										
								SHEET 1 OF 32													

1. SCOPE

1.1 Scope. This drawing documents two product assurance class levels consisting of high reliability (device classes Q and M) and space application (device class V). A choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of Radiation Hardness Assurance (RHA) levels are reflected in the PIN.

1.2 PIN. The PIN is as shown in the following example:



1.2.1 RHA designator. Device classes Q and V RHA marked devices meet the MIL-PRF-38535 specified RHA levels and are marked with the appropriate RHA designator. Device class M RHA marked devices meet the MIL-PRF-38535, appendix A specified RHA levels and are marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device.

1.2.2 Device type(s). The device type(s) identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>	<u>Access time</u>
01	4013-10	13000 gate programmable array	10 ns
02	4013-6	13000 gate programmable array	6 ns

1.2.3 Device class designator. The device class designator is a single letter identifying the product assurance level as follows:

<u>Device class</u>	<u>Device requirements documentation</u>
M	Vendor self-certification to the requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A
Q or V	Certification and qualification to MIL-PRF-38535

1.2.4 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
X	CMGA10-P223	223	Pin grid array package
Y	see figure 1	228	Quad flat package
Z	see figure 1	228	Quad flat package

1.2.5 Lead finish. The lead finish is as specified in MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 2

1.3 Absolute maximum ratings. 1/ 2/

Supply voltage range to ground potential (V_{CC})	-0.5 V dc to +7.0 V dc
DC input voltage range (V_{IN})	-0.5 V dc to $V_{CC} + 5.0$ V dc
Voltage applied to three-state output (V_{IS})	-0.5 V dc to $V_{CC} + 5.0$ V dc
Thermal resistance, junction-to-case (θ_{JC})	See MIL-STD-1835
Thermal resistance, junction-to-ambient (θ_{JA})	+50°C/W
Power dissipation (P_D)	2.0 W
Junction temperature (T_J)	+150°C 3/
Lead temperature (soldering, 10 seconds)	+260°C
Storage temperature range	-65°C to +150°C

1.4 Recommended operating conditions.

Supply voltage relative to ground (V_{CC})	+4.5 V dc minimum to +5.5 V dc maximum
Input high voltage (V_{IH})	2.0 V dc to V_{CC}
Input low voltage (V_{IL})	0 V dc to 0.8 V dc
Maximum input signal transition time (t_{IN})	250 ns
Case operating temperature range (T_C)	-55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

DEPARTMENT OF DEFENSE

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

STANDARDS

DEPARTMENT OF DEFENSE

MIL-STD-883 - Test Method Standard Microcircuits.
 MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

HANDBOOKS

DEPARTMENT OF DEFENSE

MIL-HDBK-103 - List of Standard Microcircuit Drawings.
 MIL-HDBK-780 - Standard Microcircuit Drawings.

(Unless otherwise indicated, copies of the specification, standards, and handbooks are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

- 1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.
- 2/ All voltage values in this drawing are with respect to V_{SS} .
- 3/ Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions in accordance with method 5004 of MIL-STD-883.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 3

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation.

ELECTRONIC INDUSTRIES ALLIANCE (EIA)

JESD 78 - IC Latch-Up Test.

(Application for copies should be addressed to the Electronic Industries Alliance, 2500 Wilson Boulevard, Arlington, VA 22201-3834.)

2.3 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements for device classes Q and V shall be in accordance with MIL-PRF-38535 and as specified herein or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. The individual item requirements for device class M shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535 and herein for device classes Q and V or MIL-PRF-38535, appendix A and herein for device class M.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.4 herein and figure 1.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 2.

3.2.4 Logic block diagram. The logic block diagram shall be as specified on figure 3 .

3.3 Electrical performance characteristics and postirradiation parameter limits. Unless otherwise specified herein, the electrical performance characteristics and postirradiation parameter limits are as specified in table I and shall apply over the full case operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table IIA. The electrical tests for each subgroup are defined in table I.

3.5 Marking. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked as listed in MIL-HDBK-103. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device. For RHA product using this option, the RHA designator shall still be marked. Marking for device classes Q and V shall be in accordance with MIL-PRF-38535. Marking for device class M shall be in accordance with MIL-PRF-38535, appendix A.

3.5.1 Certification/compliance mark. The certification mark for device classes Q and V shall be a "QML" or "Q" as required in MIL-PRF-38535. The compliance mark for device class M shall be a "C" as required in MIL-PRF-38535, appendix A.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 4

3.6 Certificate of compliance. For device classes Q and V, a certificate of compliance shall be required from a QML-38535 listed manufacturer in order to supply to the requirements of this drawing (see 6.6.1 herein). For device class M, a certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6.2 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply for this drawing shall affirm that the manufacturer's product meets, for device classes Q and V, the requirements of MIL-PRF-38535 and herein or for device class M, the requirements of MIL-PRF-38535, appendix A and herein.

3.7 Certificate of conformance. A certificate of conformance as required for device classes Q and V in MIL-PRF-38535 or for device class M in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change for device class M. For device class M, notification to DSCC-VA of change of product (see 6.2 herein) involving devices acquired to this drawing is required for any change as defined in MIL-PRF-38535, appendix A.

3.9 Verification and review for device class M. For device class M, DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

3.10 Microcircuit group assignment for device class M. Device class M devices covered by this drawing shall be in microcircuit group number 42 (see MIL-PRF-38535, appendix A).

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. For device classes Q and V, sampling and inspection procedures shall be in accordance with MIL-PRF-38535 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein. For device class M, sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. For device classes Q and V, screening shall be in accordance with MIL-PRF-38535, and shall be conducted on all devices prior to qualification and technology conformance inspection. For device class M, screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection.

4.2.1 Additional criteria for device class M.

- a. Delete the sequence specified as initial (preburn-in) electrical parameters through interim (postburn-in) electrical parameters of method 5004 and substitute lines 1 through 6 of table IIA herein.
 - (1) The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015.
 - (2) $T_A = +125^\circ\text{C}$, minimum.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.

4.2.2 Additional criteria for device classes Q and V.

- a. The burn-in test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The burn-in test circuit shall be maintained under document revision level control of the device manufacturer's Technology Review Board (TRB) in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.
- b. Interim and final electrical test parameters shall be as specified in table IIA herein.
- c. Additional screening for device class V beyond the requirements of device class Q shall be as specified in MIL-PRF-38535, appendix B.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 5

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
High level output voltage	V _{OH}	V _{CC} = 4.5 V, I _{OH} = -4.0 mA	1, 2, 3	All	2.4		V
Low level output voltage <u>1/</u>	V _{OL}	V _{CC} = 5.5 V, I _{OL} = 4.0 mA,	1, 2, 3	All		0.4	V
Quiescent LCA supply current <u>2/</u>	I _{CCO}	V _{CC} = V _{IN} = 5.5 V	1, 2, 3	All		50	mA
Input leakage current	I _{IL}	V _{IN} = 0 V and 5.5 V, V _{CC} = 5.5 V	1, 2, 3	All	-10	+10	μA
Pad pull-up current (when selected)	I _{RIN}	V _{IN} = 0 V	1, 2, 3	All		0.5	mA
Horizontal long line pull-up current (when selected)	I _{RLL}	At logic low	1, 2, 3	All		5.0	mA
Input capacitance	C _{IN}	See 4.4.1e	4, 5, 6	All		16	pF
Functional test	FT	See 4.4.1c	7, 8A, 8B	All			
Interconnect + t _{PID} + t _{OPS} + t _{ILO}	t _{B1}		9,10,11	01		321.5	ns
				02		199	
Interconnect + t _{PID} + t _{HHO} + t _{OPS}	t _{B2}		9, 10, 11	01		278.5	ns
				02		225.6	
Interconnect + t _{PID} + t _{OPS} + t _{IHO}	t _{B3}		9, 10, 11	01		417.5	ns
				02		247	
Interconnect + t _{PID} + t _{OPS} + t _{RIO}	t _{B4}		9, 10, 11	01		446.4	ns
				02		274	
Interconnect + t _{CKO} + t _{CK} + t _{CKI}	t _{B5}		9, 10, 11	01		22.6	ns
				02		12.6	
Interconnect + t _{CKO} + t _{HIHCK} + t _{CKHH}	t _{B6}	9, 10, 11	01		20.7	ns	
			02		13.6		
Interconnect + t _{CKO} + t _{HIHCK} + t _{CKIH}	t _{B7}	9, 10, 11	01		26.6	ns	
			02		14.6		
Interconnect + t _{CKO} + t _{DICK} + t _{CKDI}	t _{B8}	9, 10, 11	01		18.7	ns	
			02		10.6		
Interconnect + t _{CKO} + t _{ECCK} + t _{CKEC}	t _{B9}	9, 10, 11	01		23.6	ns	
			02		13.6		
Interconnect + t _{PID} + t _{OPS} + t _{OPCY} + t _{SUM} - t _{BYP}	t _{B10}	9, 10, 11	01		477.1	ns	
			02		355.8		

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 6

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Interconnect + t _{PID} + t _{OPS} + t _{ASCY} + t _{SUM} - t _{BYP}	t _{B11}		9, 10, 11	01		548	ns
				02		380.9	
Interconnect + t _{PID} + t _{OPS} + t _{INCY} + t _{SUM}	t _{B12}		9, 10, 11	01		271.7	ns
				02		207.3	
Interconnect + t _{PID} + t _{OPS} + t _{INCY} + t _{SUM} + t _{BYP}	t _{B13}		9, 10, 11	01		108.9	ns
				02		78.6	
WIDE DECODER SWITCHING CHARACTERISTICS							
Full length, both pull-ups inputs from IOB I-pins	T _{WAF}	See figures 3 and 4 as applicable. <u>3/</u>	<u>4/</u>	All		15	ns
Full length, both pull-ups inputs from internal logic	T _{WAF_L}		<u>4/</u>	All		18	ns
Half length, one pull-up inputs from IOB I-pins	T _{WAO}		<u>4/</u>	All		15	ns
Half length, one pull-up inputs from internal logic	T _{WAO_L}		<u>4/</u>	All		18	ns
CLB SWITCHING CHARACTERISTICS							
Combinatorial delay F/G inputs to X/Y outputs	T _{ILO}	See figures 3 and 4, as applicable.	<u>5/</u>	01		10	ns
				02		6	
Combinatorial delay F/G inputs via H' to X/Y outputs	T _{IHO}		<u>5/</u>	01		14	ns
				02		8	
Combinatorial delay C inputs via H' to X/Y outputs	T _{HHO}		<u>5/</u>	01		8	ns
				02		7	
CLB fast carry logic operand inputs (F1, F2, G1, G4) to C _{OUT}	T _{OPCY}		<u>6/</u>	01		8	ns
				02		7	
CLB fast carry logic add/ subtract input (F3) to C _{OUT}	T _{ASCY}		<u>6/</u>	01		11	ns
				02		8	
CLB fast carry logic initialization inputs (F1,F3) to C _{OUT}	T _{INCY}		<u>6/</u>	All		6	ns
CLB fast carry logic C _{IN} through function generators to X/Y outputs	T _{SUM}		<u>6/</u>	01		12	ns
		02			8		
CLB fast carry logic C _{IN} to C _{OUT} , bypass function generators	T _{BYP}	<u>6/</u>	01		3	ns	
			02		2		

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 7

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
CLB SWITCHING CHARACTERISTICS - Continued.							
Sequential delays clock K to outputs Q	T _{CKO}	See figures 3 and 4, as applicable	5/	01		9	ns
				02		5	
Set-up time before clock K, F/G inputs	T _{ICK}		5/	01	11		ns
				02	6		
Set-up time before clock K, F/G inputs via H'	T _{IHCK}		5/	01	15		ns
				02	8		
Set-up time before clock K, C inputs via H1	T _{HHCK}		5/	01	9		ns
				02	7		
Set-up time before clock K, C inputs via DIN	T _{DICK}		5/	01	7		ns
				02	4		
Set-up time before clock K, C inputs via EC	T _{ECCK}		5/	01	12		ns
				02	7		
Set-up time before clock K, C inputs via S/R, going low (inactive)	T _{RCK}		4/	01	10		ns
				02	6		
Set-up time before clock K, C _{IN} input via F'/G'	T _{CCK}		4/	All	8		ns
Set-up time before clock K, C _{IN} input via F'/G' and H'	T _{CHCK}		4/	All	10		ns
Hold time after clock K, F/G inputs	T _{CKI}		5/	All	0		ns
Hold time after clock K, F/G inputs via H'	T _{CKIH}		5/	All	0		ns
Hold time after clock K, C inputs via H1	T _{CKHH}		5/	All	0		ns
Hold time after clock K,C inputs via DIN	T _{CKDI}		5/	All	0		ns
Hold time after clock K, C inputs via EC	T _{CKEC}	5/	All	0		ns	
Hold time after clock K, C inputs via S/R, going low (inactive)	T _{CKR}	4/	All	0		ns	
Clock high time	T _{CH}	4/	01	5.5		ns	
			02	5			
Clock low time	T _{CL}	4/	01	5.5		ns	
			02	5			
Set/Reset direct width (high)	T _{RPW}	4/	01	6		ns	
			02	5			

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 8

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
CLB SWITCHING CHARACTERISTICS - continued.							
Set/Reset direct delay, from C to Q	T _{RIO}	See figures 3 and 4, as applicable.	<u>5/</u>	01		15	ns
				02		9	
Master set/reset width (high or low)	T _{MRW}		<u>4/</u>	01	120		ns
		02		110			
Master set/reset delay from global set/reset net to Q	T _{MRO}	<u>4/</u>	01		130	ns	
			02		120		
CLB SWITCHING CHARACTERISTICS (RAM OPTION)							
Read operation, address read cycle time (16 X 2)	T _{RC}	See figures 3 and 4, as applicable. <u>7/</u>	<u>8/</u>	01	12		ns
				02	7		
Read operation, address read cycle time (32 X 1)	T _{RCT}		<u>8/</u>	01	15		ns
				02	10		
Read operation data valid after address change (no write enable) (16 X 2)	T _{ILO}		<u>8/</u>	01		10	ns
				02		6	
Read operation data valid after address change (no write enable) (32 X 1)	T _{IHO}		<u>8/</u>	01		14	ns
				02		8	
Read during write, clocking data into flip flop address setup time before clock K (16 X 2)	T _{ICK}		<u>8/</u>	01	11		ns
				02	6		
Read during write, clocking data into flip flop address setup time before clock K (32 X 1)	T _{IHCK}		<u>8/</u>	01	15		ns
				02	8		
Read during write, data valid after WE going active (16 X 2)	T _{WO}		<u>8/</u>	01		15	ns
				02		12	
Read during write, (DIN stable before WE) (32 X 1)	T _{WOT}		<u>8/</u>	01		27	ns
		02			15		
Read during write, data valid after DIN (16 X 2)	T _{DO}	<u>8/</u>	01		19	ns	
			02		11		
Read during write, (DIN change during WE) (32 X 1)	T _{DOT}	<u>8/</u>	01		22	ns	
			02		14		
Read during write, clocking data into flip flop, WE setup time before clock K (16 X 2)	T _{WCK}	<u>8/</u>	01	15		ns	
			02	12			

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 9

TABLE I. Electrical performance characteristics - continued.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
CLB SWITCHING CHARACTERISTICS (RAM OPTION) - Continued.							
Read during write, clocking data into flip flop, WE setup time before clock K (32 X 1)	T _{WCKT}	See figures 3 and 4, as applicable 7/	8/	01	27		ns
					02	15	
Read during write, clocking data into flip flop, data setup time before clock K (16 X 2)	T _{DCK}		8/	01	19		ns
					02	11	
Read during write, clocking data into flip flop, data setup time before clock K (32 X 1)	T _{DCKT}		8/	01	22		ns
					02	14	
Write operation, address write cycle time (16 X 2)	T _{WC}		8/	01	16		ns
					02	9	
Write operation, address write cycle time (32 X 1)	T _{WCT}		8/	01	16		ns
					02	9	
Write operation, write enable pulse width (high) (16 X 2)	T _{WP}		8/	01	12		ns
					02	5	
Write operation, write enable pulse width (high) (32 X 1)	T _{WPT}		8/	01	12		ns
					02	5	
Write operation, address setup time before beginning of WE (16 X 2)	T _{AS}		8/	All	2		ns
Write operation, address setup time before beginning of WE (32 X 1)	T _{AST}		8/	All	2		ns
Write operation, address hold time after end of WE (16 X 2)	T _{AH}		8/	All	2		ns
Write operation, address hold time after end of WE (32 X 1)	T _{AHT}		8/	All	2		ns
Write operation, DIN setup time before end of WE (16 X 2)	T _{DS}		8/	All	4		ns
Write operation, DIN setup time before end of WE (32 X 1)	T _{DST}		8/	All	5		ns
Write operation, DIN hold time after end of WE	T _{DHT}		8/	All	2		ns

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 10

TABLE I. Electrical Performance Characteristics - continued.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
IOB SWITCHING CHARACTERISTICS							
Input propagation delay, pad to I1, I2	T _{PID}	See figures 3 and 4 as applicable. 9/ 10/	5/	All		4	ns
Input propagation delay, pad to I1, I2, via transparent latch (fast)	T _{PLI}		4/	01		13	ns
				02		8	
Input propagation delay, pad to I1, I2, via transparent latch (with delay)	T _{PDLI}		4/	01		30	ns
				02		26	
Input propagation delay, clock (IK) to I1, I2, (flip-flop)	T _{IKRI}		4/	01		8.5	ns
		02			8		
Input propagation delay, clock (IK) to I1, I2, (latch enable)	T _{IKLI}	4/	01		9	ns	
			02		8		
Setup time, pad to clock (IK), fast	T _{PICK}	See figures 3 and 4 as applicable. 9/ 10/ 11/	4/	01	9	ns	
Setup time, pad to clock (IK), with delay	T _{PICKD}		4/	02	7		
				01	35	ns	
Hold time, pad to clock (IK), fast	T _{IKPI}		4/	All			1
				All		negative	ns
Output propagation delay clock (OK) to pad, (fast)	T _{OKPOF}		See figures 3 and 4 as applicable. 9/ 10/	4/	01	11	ns
Output propagation delay clock (OK) to pad, (slew rate limited)	T _{OKPOS}	4/		02	7.5		
				01	16	ns	
Output propagation delay output (O) to pad (fast)	T _{OPF}	4/		02	11.5		
				01	10	ns	
Output propagation delay output (O) to pad (slew rate limited)	T _{OPS}	5/		02	9		
				01	15	ns	
Output propagation delay 3- state to pad begin hi-Z (fast)	T _{TSHZF}	4/		02	13		
				01	10	ns	
Output propagation delay 3- state to pad active and valid (fast)	T _{TSONF}	4/		02	9		
				01	15	ns	
Output propagation delay 3- state to pad active and valid (slew rate limited)	T _{TSONS}	4/		02	13		
				01	20	ns	
				02	17		

See footnotes at end of table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 11

TABLE I. Electrical Performance Characteristics - continued.

Test	Symbol	Conditions 4.5 V ≤ V _{CC} ≤ 5.5 V -55°C ≤ T _C ≤ +125°C unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
IOB SWITCHING CHARACTERISTICS - continued							
Setup time, output (O) to clock (OK)	T _{OOK}	See figures 3 and 4 as applicable. 9/ 10/	4/	01	13		ns
				02	8		
Hold time, output (O) to clock (OK)	T _{OKO}		4/	All		0	ns
Clock high or low time	T _{CH} / T _{CL}		4/	01	6		ns
				02	5		
Global set/reset delay from GSR net through Q to I1, I2	T _{RRI}		4/	01		20	ns
				02		14.5	
Global set/reset delay from GSR net to pad	T _{RPO}		4/	01		23	ns
				02		18	
Global set/reset GSR width	T _{MRW}		4/	All	21		ns

- 1/ With 50 percent of the outputs simultaneously sinking 4 mA.
- 2/ With no output current loads, no active input or long line pull-resistors, all package pins at V_{CC} or GND, and the LCA configured with a MakeBits "tie" option.
- 3/ These delays are specified from the decoder input to the decoder output. For pad-to-pad delays, add the input delay (T_{PID}) and output delay (T_{OPF} or T_{OPS}).
- 4/ Parameter is not tested but is guaranteed by characterization data which is taken at initial device introduction, prior to the introduction of significant changes, and at least twice yearly.
- 5/ Parameter is not directly tested. Devices are first 100 percent functionality tested. Benchmark patterns (t_{B1} - t_{B13}) are then used to determine the compliance of this parameter. Characterization data is taken initially and after any design or process change which may affect this parameter.
- 6/ Benchmark patterns (t_{B1} - t_{B13}) are used to determine compliance to this parameter.
- 7/ Timing for the 16 X 1 RAM option is identical to 16 X 2 RAM timing.
- 8/ Values indicated are guaranteed by characterization data if application note, provided by manufacturer, is followed. If application note is not followed, indicated values are typical only.
- 9/ Timing is measured at pin threshold, with 50 pF external capacitive loads including test fixture. Slew rate limited output rise/fall times are approximately two times longer than fast output rise/fall times. A maximum total external capacitive load for simultaneous fast mode switching in the same direction is 200 pF per power/ground pin pair. For slew rate limited outputs this total is two times larger. Exceeding this maximum capacitive load can result in ground bounce of greater than 1.5 V amplitude, less than 5 ns duration, which might cause problems when the LCA drives clocks and other asynchronous signals.
- 10/ Voltage levels of unused (bonded and unbonded) pads must be valid logic levels. Each can be configured with the internal pull-up or pull-down resistor or alternatively configured as a driven output or be driven from an external source.
- 11/ Input pad setup times and hold times are specified with respect to the internal clock (IK). To calculate system setup time, subtract clock delay (clock pad to IK) from the specified input pad setup time value, but do not subtract below zero. "Negative" hold time means that the delay in the input data is adequate for the external system hold time to be zero, provided the input clock uses the global signal distribution from pad to IK.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 12

Case Y




FIGURE 1. Case outline.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 13

Case Y - Continued

Inches	mm		Inches	mm
.002	0.05		.035	0.89
.004	0.10		.040	1.02
.005	0.13		.043	1.09
.008	0.20		.050	1.27
.009	0.23		.075	1.91
.0125	0.32		.090	2.29
.016	0.41		.130	3.30
.0175	0.445		.900	22.86
.020	0.51		1.550	39.37
.021	0.53		1.920	48.77
.025	0.64		2.300	58.42
.030	0.76		2.500	63.50

NOTES:

1. Dimensions are in inches.
2. The US government preferred system of measurement is the metric SI system. However, this item was originally designed using inch-pound units of measurement. In the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.
3. Top side mark location, product mark is located on the nonlid side of package; i.e., lid side facing down. When mounted in this position, the pin out is clockwise.
4. The leads of this package style shall be protected from mechanical distortion and damage such that dimensions pertaining to relative lead/body "true positions" and lead "coplanarity" are always maintained until the next higher level package attachment process is complete. Package lead protection mechanisms (tie bars) are shown on the drawing for reference only. When microcircuit devices contained in this package style are shipped for use in Government equipment, or shipped directly to the Government as spare parts or mechanical qualification samples, lead "true position" and "coplanarity" protection shall be in place.

FIGURE 1. Case outline - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 14

Case Z




FIGURE 1. Case outline - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 15

Case Z - Continued

Inches	mm		Inches	mm
.002	0.05		.035	0.89
.004	0.10		.040	1.02
.005	0.13		.043	1.09
.008	0.20		.050	1.27
.009	0.23		.075	1.91
.0125	0.32		.090	2.29
.016	0.41		.130	3.30
.0175	0.445		.900	22.86
.020	0.51		1.550	39.37
.021	0.53		1.920	48.77
.025	0.64		2.300	58.42
.030	0.76		2.500	63.50

NOTES:

1. Dimensions are in inches.
2. The US government preferred system of measurement is the metric SI system. However, this item was originally designed using inch-pound units of measurement. In the event of conflict between the metric and inch-pound units, the inch-pound units shall take precedence.
3. Top side mark location, product mark is located on the lided side of package; i.e., lid side facing up. When mounted in this position, the pin out is counterclockwise.
4. The leads of this package style shall be protected from mechanical distortion and damage such that dimensions pertaining to relative lead/body "true positions" and lead "coplanarity" are always maintained until the next higher level package attachment process is complete. Package lead protection mechanisms (tie bars) are shown on the drawing for reference only. When microcircuit devices contained in this package style are shipped for use in Government equipment, or shipped directly to the Government as spare parts or mechanical qualification samples, lead "true position" and "coplanarity" protection shall be in place.

FIGURE 1. Case outline - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 16

Case outline X

Device type	All	Device type	All	Device type	All
Terminal number	Terminal symbol	Terminal number	Terminal symbol	Terminal number	Terminal symbol
A2	I/O (TDI)	C4	I/O (A17)	E16	I/O (HDC)
A3	I/O	C5	I/O	E17	I/O (LDC)
A4	I/O	C6	I/O	E18	I/O
A5	I/O	C7	GND	F1	I/O
A6	I/O	C8	I/O	F2	I/O
A7	I/O	C9	I/O	F3	I/O (A12)
A8	I/O	C10	I/O	F4	I/O
A9	I/O	C11	I/O	F15	I/O
A10	I/O	C12	GND	F16	I/O
A11	I/O	C13	I/O	F17	I/O
A12	I/O	C14	I/O	F18	I/O
A13	I/O	C15	M1	G1	I/O (A10)
A14	I/O	C16	M2	G2	I/O (A11)
A15	I/O	C17	I/O	G3	GND
A16	I/O	C18	I/O	G4	I/O
A17	I/O	D1	I/O	G15	I/O
A18	M0	D2	I/O (A13)	G16	GND
B1	I/O	D3	V _{CC}	G17	I/O
B2	SGCK1 (A15, I/O)	D4	GND	G18	I/O
B3	I/O	D5	I/O	H1	I/O
B4	I/O (TCK)	D6	I/O	H2	I/O
B5	I/O	D7	I/O	H3	I/O
B6	I/O	D8	I/O	H4	I/O
B7	I/O (TMS)	D9	GND	H15	I/O
B8	I/O	D10	V _{CC}	H16	I/O
B9	I/O	D11	I/O	H17	I/O
B10	I/O	D12	I/O	H18	I/O
B11	I/O	D13	I/O	J1	I/O
B12	I/O	D14	I/O	J2	I/O (A9)
B13	I/O	D15	GND	J3	I/O (A8)
B14	I/O	D16	V _{CC}	J4	V _{CC}
B15	I/O	D17	I/O	J15	V _{CC}
B16	SGCK2 (I/O)	D18	I/O	J16	I/O ($\overline{\text{ERR}}$, $\overline{\text{INIT}}$)
B17	PGCK2 (I/O)	E1	I/O	J17	I/O
B18	I/O	E2	I/O	J18	I/O
C1	I/O	E3	I/O		
C2	I/O (A14)	E4	I/O		
C3	PGCK1 (A16, I/O)	E15	I/O		

FIGURE 2. Terminal connections.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 17

Case outline X - Continued.

Device type	All	Device type	All	Device type	All
Terminal number	Terminal symbol	Terminal number	Terminal symbol	Terminal number	Terminal symbol
K1	I/O	P18	I/O	U3	I/O (D0, DIN)
K2	I/O (A6)	R1	I/O	U4	I/O
K3	I/O (A7)	R2	I/O	U5	I/O
K4	GND	R3	GND	U6	I/O
K15	GND	R4	V _{CC}	U7	I/O
K16	I/O	R5	I/O	U8	I/O
K17	I/O	R6	I/O	U9	I/O (\overline{RS})
K18	I/O	R7	I/O	U10	I/O (D4)
L1	I/O	R8	I/O	U11	I/O
L2	I/O	R9	GND	U12	I/O (D5)
L3	I/O	R10	V _{CC}	U13	I/O
L4	I/O	R11	I/O	U14	I/O
L15	I/O	R12	I/O	U15	I/O
L16	I/O	R13	I/O	U16	PGCK3 (I/O)
L17	I/O	R14	I/O	U17	DONE
L18	I/O	R15	V _{CC}	U18	I/O
M1	I/O (A5)	R16	GND	V1	CCLK
M2	I/O (A4)	R17	I/O	V2	I/O (\overline{RCLK} - \overline{BUSY} /RDY)
M3	GND	R18	I/O	V3	I/O (D1)
M4	I/O	T1	I/O	V4	I/O
M15	I/O	T2	I/O (CS1, A2)	V5	I/O
M16	GND	T3	I/O (A0, \overline{WS})	V6	I/O
M17	I/O	T4	SGCK4 (DOUT, I/O)	V7	I/O (D2)
M18	I/O	T5	I/O	V8	I/O
N1	I/O	T6	I/O	V9	I/O
N2	I/O	T7	GND	V10	I/O
N3	I/O (A3)	T8	I/O	V11	I/O
N4	I/O	T9	I/O (D3)	V12	I/O ($\overline{CS0}$)
N15	I/O	T10	I/O	V13	I/O
N16	I/O	T11	I/O	V14	I/O
N17	I/O	T12	GND	V15	I/O
N18	I/O	T13	I/O	V16	I/O
P1	I/O	T14	I/O	V17	I/O (D6)
P2	I/O	T15	I/O (D7)	V18	\overline{PROG}
P3	I/O	T16	SGCK3 (I/O)		
P4	I/O	T17	I/O		
P15	I/O	T18	I/O		
P16	I/O	U1	PGCK4 (I/O, A1)		
P17	I/O	U2	TD0		

FIGURE 2. Terminal connections - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 18

Case outline Y and Z

Device type	All	Device type	All	Device type	All
Terminal number	Terminal symbol	Terminal number	Terminal symbol	Terminal number	Terminal symbol
1	V _{SS}	45	I/O	89	I/O
2	BUFGP_TL_A16_	46	I/O	90	I/O
	PGCK1_I/O	47	I/O	91	I/O
3	A17_I/O	48	I/O	92	I/O
4	I/O	49	I/O	93	I/O
5	I/O	50	I/O	94	I/O
6	TDI_I/O	51	I/O	95	V _{CC}
7	TCK_I/O	52	I/O	96	I/O
8	I/O	53	I/O	97	I/O
9	I/O	54	BUFGS_BL_SGCK2	98	I/O
10	I/O		_I/O	99	I/O
11	I/O	55	M1	100	V _{SS}
12	I/O	56	V _{SS}	101	I/O
13	I/O	57	M0	102	I/O
14	V _{SS}	58	V _{CC}	103	I/O
15	I/O	59	M2	104	I/O
16	I/O	60	BUFGS_BL_PGCK2	105	I/O
17	TMS_I/O		_I/O	106	I/O
18	I/O	61	HDC_I/O	107	I/O
19	I/O	62	I/O	108	I/O
20	I/O	63	I/O	109	I/O
21	I/O	64	I/O	110	I/O
22	I/O	65	LDC_I/O	111	I/O
23	I/O	66	I/O	112	BUFGS_BR_SGCK3_
24	I/O	67	I/O		I/O
25	I/O	68	I/O	113	V _{SS}
26	I/O	69	I/O	114	DONE
27	V _{SS}	70	I/O	115	V _{CC}
28	V _{CC}	71	I/O	116	/PROG
29	I/O	72	V _{SS}	117	D7_I/O
30	I/O	73	I/O	118	BUFGP_BR_PGCK3_
31	I/O	74	I/O		I/O
32	I/O	75	I/O	119	I/O
33	I/O	76	I/O	120	I/O
34	I/O	77	I/O	121	I/O
35	I/O	78	I/O	122	I/O
36	I/O	79	I/O	123	D6_I/O
37	V _{CC}	80	I/O	124	I/O
38	I/O	81	I/O	125	I/O
39	I/O	82	I/O	126	I/O
40	I/O	83	I/O	127	I/O
41	I/O	84	/ERR_INIT_I/O	128	I/O
42	V _{SS}	85	V _{CC}	129	V _{SS}
43	I/O	86	V _{SS}	130	I/O
44	I/O	87	I/O	131	I/O
45	I/O	88	I/O	132	I/O
				133	I/O

FIGURE 2. Terminal connections - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 19

Case outline Y and Z - Continued.

Device type	All	Device type	All	Device type	All
Terminal number	Terminal symbol	Terminal number	Terminal symbol	Terminal number	Terminal symbol
134	D5_I/O	176	I/O	223	I/O
135	/CS0_I/O	177	I/O	224	I/O
136	I/O	178	CS1_A2_I/O	225	I/O
137	I/O	179	A3_I/O	226	A14_I/O
138	I/O	180	I/O	227	BUFGS_TL_SGCK1_
139	I/O	181	I/O		A15_I/O
140	D4_I/O	182	I/O	228	Vcc
141	I/O	183	I/O		
142	Vcc	184	I/O		
143	Vss	185	I/O		
144	D3_I/O	186	Vss		
145	/RS_I/O	187	I/O		
146	I/O	188	I/O		
147	I/O	189	I/O		
148	I/O	190	I/O		
149	I/O	191	Vcc		
150	D2_I/O	192	A4_I/O		
151	I/O	193	A5_I/O		
152	VCC	194	I/O		
153	I/O	195	I/O		
154	I/O	196	I/O		
155	I/O	197	I/O		
156	I/O	198	A6_I/O		
157	Vss	199	A7_I/O		
158	I/O	200	Vss		
159	I/O	201	Vcc		
160	I/O	202	A8_I/O		
161	I/O	203	A9_I/O		
162	I/O	204	I/O		
163	I/O	205	I/O		
164	D1_I/O	206	I/O		
165	BUSY_/RDY_	207	I/O		
	RCLK_I/O	208	A10_I/O		
166	I/O	209	A11_I/O		
167	I/O	210	Vcc		
168	D0_DIN_I/O	211	I/O		
169	BUFGS_TR_	212	I/O		
	SGCK4_DOUT_	213	I/O		
	I/O	214	I/O		
170	CCLK	215	Vss		
171	VCC	216	I/O		
172	TDO	217	I/O		
173	Vss	218	I/O		
174	A0_WS_I/O	219	I/O		
175	BUFGP_TR_	220	A12_I/O		
	PGCK4_A1_I/O	221	A13_I/O		
		222	I/O		

FIGURE 2. Terminal connections - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 20




FIGURE 3. Logic block diagrams.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 21




FIGURE 3. Logic block diagrams - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 22




FIGURE 3. Logic block diagrams - Continued.

**STANDARD
MICROCIRCUIT DRAWING**
DEFENSE SUPPLY CENTER COLUMBUS
COLUMBUS, OHIO 43216-5000

SIZE
A

5962-94730

REVISION LEVEL
D

SHEET
23

BOUNDARY SCAN LOGIC




FIGURE 3. Logic block diagrams - Continued.

FIGURE 3. Truth table.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 24

GENERAL LOGIC CELL ARRAY (LCA) SWITCHING CHARACTERISTICS




FIGURE 4. Timing diagrams and switching characteristics.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 25

CONFIGURABLE LOGIC BLOCK (CLB) SWITCHING CHARACTERISTICS




FIGURE 4. Timing diagrams and switching characteristics - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 26

I/O BLOCK (IOB) SWITCHING CHARACTERISTICS




FIGURE 4. Timing diagrams and switching characteristics - Continued.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 27

4.3 Qualification inspection for device classes Q and V. Qualification inspection for device classes Q and V shall be in accordance with MIL-PRF-38535. Inspections to be performed shall be those specified in MIL-PRF-38535 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4 Conformance inspection. Technology conformance inspection for classes Q and V shall be in accordance with MIL-PRF-38535 including groups A, B, C, D, and E inspections and as specified herein. Quality conformance inspection for device class M shall be in accordance with MIL-PRF-38535, appendix A and as specified herein. Inspections to be performed for device class M shall be those specified in method 5005 of MIL-STD-883 and herein for groups A, B, C, D, and E inspections (see 4.4.1 through 4.4.4).

4.4.1 Group A inspection.

- a. Tests shall be as specified in table IIA herein.
- b. Subgroups 5 and 6 of table I of method 5005 of MIL-STD-883 shall be omitted.
- c. For device class M, subgroups 7 and 8 tests shall be sufficient to verify the truth table. For device classes Q and V, subgroups 7 and 8 shall include verifying the functionality of the device.
- d. O/V (latch-up) tests shall be measured only for initial qualification and after any design or process changes which may affect the performance of the device. For device class M, procedures and circuits shall be maintained under document revision level control by the manufacturer and shall be made available to the preparing activity or acquiring activity upon request. For device classes Q and V, the procedures and circuits shall be under the control of the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the preparing activity or acquiring activity upon request. Testing shall be on all pins, on five devices with zero failures. Latch-up test shall be considered destructive. Information contained in JESD 78 may be used for reference.
- e. Subgroup 4 (C_{IN} measurements) shall be measured only for initial qualification and after any process or design changes which may affect input capacitance. Capacitance shall be measured between the designated terminal and GND at a frequency of 1 MHz. Sample size is 15 devices with no failures, and all input terminals tested.

4.4.2 Group C inspection. The group C inspection end-point electrical parameters shall be as specified in table II herein.

4.4.2.1 Additional criteria for device class M. Steady-state life test conditions, method 1005 of MIL-STD-883:

- a. Test condition D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.
- b. $T_A = +125^{\circ}\text{C}$, minimum.
- c. Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.4.2.2 Additional criteria for device classes Q and V. The steady-state life test duration, test condition and test temperature, or approved alternatives shall be as specified in the device manufacturer's QM plan in accordance with MIL-PRF-38535. The test circuit shall be maintained under document revision level control by the device manufacturer's TRB in accordance with MIL-PRF-38535 and shall be made available to the acquiring or preparing activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 28

TABLE IIA. Electrical test requirements. 1/ 2/ 3/ 4/ 5/ 6/ 7/

Line no.	Test requirements	Subgroups (in accordance with MIL-STD-883, method 5005, table I)	Subgroups (in accordance with MIL-PRF-38535, table III)	
		Device class M	Device class Q	Device class V
1	Interim electrical parameters (see 4.2)		1,7,9	1,7,9
2	Static burn-in (method 1015)	Required	Required	Required
3	Same as line 1			1* Δ
4	Dynamic burn-in (method 1015)	Not required	Not required	Not required
5	Final electrical parameters	1*,2,3,7*, 8A,8B,9,10, 11	1*,2,3,7*, 8A,8B,9,10, 11	1*,2,3,7*, 8A,8B,9, 10,11
6	Group A test requirements	1,2,3,4**,7, 8A,8B,9,10, 11	1,2,3,4**,7, 8A,8B,9,10, 11	1,2,3,4**,7, 8A,8B,9,10, 11
7	Group C end-point electrical parameters	2,3,7, 8A,8B	1,2,3,7, 8A,8B Δ	1,2,3,7, 8A,8B,9, 10,11 Δ
8	Group D end-point electrical parameters	2,3, 8A,8B	2,3, 8A,8B	2,3, 8A,8B
9	Group E end-point electrical parameters	1,7,9	1,7,9	1,7,9

1/ Blank spaces indicate tests are not applicable.

2/ Any or all subgroups may be combined when using high-speed testers.

3/ Subgroups 7 and 8 functional tests shall verify the functionality of the device.

4/ * indicates PDA applies to subgroup 1 and 7.

5/ ** see 4.4.1e.

6/ Δ indicates delta limit (see table IIB) shall be required where specified, and the delta values shall be computed with reference to the previous interim electrical parameters (see line 1).

7/ See 4.4.1d.

4.4.3 Group D inspection. The group D inspection end-point electrical parameters shall be as specified in table II herein.

4.4.4 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein).

- a. End-point electrical parameters shall be as specified in table II herein.
- b. For device classes Q and V, the devices or test vehicle shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535 for the RHA level being tested. For device class M, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38535, appendix A for the RHA level being tested. All device classes must meet the postirradiation end-point electrical parameter limits as defined in table I at T_A = +25°C ±5°C, after exposure, to the subgroups specified in table II herein.
- c. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 29

TABLE IIB. Delta limits at +25°C.

Parameter <u>1/</u>	Device types
	All
I _{CCO} standby	±1 mA of specified limit in table I.
I _{IL}	±1 µA of specified limit in table I.

1/ The above parameter shall be recorded before and after the required burn-in and life tests to determine the delta.

4.5 Delta measurements for device classes Q and V. Delta measurements, as specified in table IIA, shall be made and recorded before and after the required burn-in screens and steady-state life tests to determine delta compliance. The electrical parameters to be measured, with associated delta limits are listed in table IIB. The device manufacturer may, at his option, either perform delta measurements or within 24 hours after burn-in perform final electrical parameter tests, subgroups 1, 7, and 9.

4.6 Programming procedures. The programming procedures shall be as specified by the device manufacturer and shall be made available upon request.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535 for device classes Q and V or MIL-PRF-38535, appendix A for device class M.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.1.1 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor prepared specification or drawing.

6.1.2 Substitutability. Device class Q devices will replace device class M devices.

6.2 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.3 Record of users. Military and industrial users should inform Defense Supply Center Columbus when a system application requires configuration control and which SMD's are applicable to that system. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0544.

6.4 Comments. Comments on this drawing should be directed to DSCC-VA, Columbus, Ohio 43216-5000, or telephone (614) 692-0547.





STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 30

6.5 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein are defined in MIL-PRF-38535, MIL-HDBK-1331, and as follows:

V _{CC}	+5.0 V SUPPLY VOLTAGE
GND	GROUND
CCLK	CONFIGURATION CLOCK
DONE	DONE
PROGRAM	PROGRAM
RCLK	READ CLOCK
M0	MODE 0
M1	MODE 1
M2	MODE 2
TDO	TEST DATA OUTPUT
TDI	TEST DATA IN
TCK	TEST CLOCK
TMS	TEST MODE SELECT
HDC	HIGH DURING CONFIGURATION
LDC	LOW DURING CONFIGURATION
INIT	INIT
PGCK1-PGCK4	PRIMARY GLOBAL INPUTS
RDY/BUSY	During peripheral parallel mode configuration, this pin indicates when the chip is ready for another byte of data to be written into it. After configuration is complete, this pin becomes a user programmed I/O pin.
CS0	CHIP SELECT, WRITE
CS1	CHIP SELECT, WRITE
WS	WRITE STROBE
RS	READ STROBE
A0-A17	ADDRESS
D0-D7	DATA
DIN	DATA INPUT
DOUT	DATA OUTPUT
I/O	INPUT/OUTPUT

6.5.1 Timing limits. The table of timing values shows either a minimum or a maximum limit for each parameter. Input requirements are specified from the external system point of view. Thus, address setup time is shown as a minimum since the system must supply at least that much time (even though most devices do not require it). On the other hand, responses from the memory are specified from the device point of view. Thus, the access time is shown as a maximum since the device never provides data later than that time.

6.5.2 Waveforms.

Waveform symbol	Input	Output
	MUST BE VALID	WILL BE VALID
	CHANGE FROM H TO L	WILL CHANGE FROM H TO L
	CHANGE FROM L TO H	WILL CHANGE FROM L TO H
	DON'T CARE ANY CHANGE PERMITTED	CHANGING STATE UNKNOWN
		HIGH IMPEDANCE

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 31

BUFFER SWITCHING CHARACTERISTICS

Test	Symbol	Conditions -55°C ≤ T _C ≤ +125°C 4.5 V ≤ V _{CC} ≤ 5.5 V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
TBUF driving a horizontal Longline (L.L.) I to L.L. while T is low (buffer active)	T _{IO1}	See note.	N/A	All		13	ns
TBUF driving a horizontal Longline (L.L.) I going low to L.L. going from resistive pull up high to active low, (TBUF configured as open drain)	T _{IO2}		N/A	All		13.5	ns
T going low to L.L. active and valid	T _{ON}		N/A	All		15.1	ns
T to L.L. inactive	T _{OFF}		N/A	All		3	ns
T going high to L.L. (inactive) with single pull-up resistor	T _{PUS}		N/A	All		36	ns
T going high to L.L. (inactive) with pair of pull-up resistors	T _{PUF}		N/A	All		17	ns

NOTE:

These values are typical. They are not tested, characterized, or guaranteed but are derived from benchmark timing patterns.

6.6 Sources of supply.

6.6.1 Sources of supply for device classes Q and V. Sources of supply for device classes Q and V are listed in QML-38535. The vendors listed in QML-38535 have submitted a certificate of compliance (see 3.6 herein) to DSCC-VA and have agreed to this drawing.

6.6.2 Approved sources of supply for device class M. Approved sources of supply for class M are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-94730
		REVISION LEVEL D	SHEET 32

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 02-04-16

Approved sources of supply for SMD 5962-94730 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535.

Standard microcircuit drawing PIN <u>1/</u>	Vendor CAGE number	Vendor similar PIN <u>2/</u>
5962-9473001MXC	<u>3/</u>	XC4013-10PG223B
5962-9473001MYC	<u>3/</u>	XC4013-10CB228B
5962-9473001MZC	<u>3/</u>	XC4013-10CB228B
5962-9473002MXC	68994	XC4013-6PG223B
5962-9473002MYC	68994	XC4013-6CB228B
5962-9473002MZC	68994	XC4013-6CB228B

1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.

2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

3/ Not available from an approved source of supply.

Vendor CAGE
number

68994

Vendor name
and address

Xilinx, Incorporated
2100 Logic Drive
San Jose, CA 95124

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.