

QUALIFIED PRODUCTS LIST

OF

FSC 5910

PRODUCTS QUALIFIED UNDER MILITARY SPECIFICATION

MIL-C-87164

CAPACITOR, FIXED, MICA DIELECTRIC, HIGH RELIABILITY

GENERAL SPECIFICATION FOR

This list has been prepared for use by or for the Government in the acquisition of products covered by Specifications MIL-C-87164. Listing of a product is not intended to and does not connote endorsement of the product by the Department of Defense. All products listed herein have been qualified under the requirements for the product as specified in the latest effective issue of the applicable specification. This list is subject to change without notice; revision or amendment of this list will be issued as necessary. The listing of a product does not release the supplier from compliance with the specification requirements.

THE ACTIVITY RESPONSIBLE FOR THIS QPL IS THE SPACE SYSTEMS CENTER, CODE 19. The activity designated as agent for all contacts relative to this QPL is the Defense Electronics Supply Center (DESC-EQ), Dayton, OH 45444-5270.

GOVERNMENT DESIGNATION	MANUFACTURER'S DESIGNATION OR TYPE NUMBER	TEST OR QUALIFICATION REFERENCE	DETAIL SPECIFI- CATION	MANUFACTURER'S NAME (ADDRESS ON LAST PAGE)
CMS03 M87164A05 (See specification sheet MIL-C-87164/5(USAF) for part numbers.) Chars. C and E in 500 volts, all cap. values and tols.	M2HRCMS03	87164-853-87	/5	Silvered Electronic Mica Company, Inc. (SEMCO) Route 66 107 Boston Post Road Willimantic, CT 06226 Plant: Same Address CAGE CODE: 61306
CMS04 M87164A01 (See specification sheet MIL-C-87164/1(USAF) for part numbers.) Chars. C and E in 500 volts, all cap. values and tols.	M2HRCMS04	87164-1090-85	/1	
CMS05 M87164A02 (See specification sheet MIL-C-87164/2(USAF) for part numbers.) Chars. C and E in 500 volts, all cap. values and tols.	M2HRCMS05	87164-1091-85	/2	
CMS06 M87164A03 (See specification sheet MIL-C-87164/3(USAF) for part numbers.) Chars. C, E, and F in 500 volts, all cap. values and tols.	M2HRCMS06	87164-1092-85	/3	
CMS07 M87164A04 (See specification sheet MIL-C-87164/4(USAF) for part numbers.) Chars. C, E and F in 500 volts, all cap. values and tols.	M2HRCMS07	87164-854-87	/4	